

REV Spreader Range

Our REV range is specially designed for all types of farming that need to deal with width constraints: vineyards, espaliered orchards, market gardening rows ...
 The steered axel feature makes our models extremely easy to manoeuvre, especially at the end of rows where there is little turning space. The spreading tables allow you to deposit materials at the base of vines or espaliered trees, or spread along several rows at a time.

Standard model

- 2 horizontal beaters (mechanical drive)
- Hydraulic drive conveyor; flow-rate control device
- U-shaped two-chain conveyor
- Standard wheels
- Standard Cardan shaft
- Front grill guard
- Mechanical and hydraulic brakes
- Lights, approved for road use - 25 km/h

Options available

- Cover
- Hinged side flaps
- Steered axel
- Hydraulic sliding door
- Hydraulic or mechanical spreading table, depending on the size of the body shell
- 2 vertical beaters (1.2 m-wide body shell)
- 1 hydraulic horizontal beater



REV2 3500 with hydraulic sliding door, réhausses ALU 30 cm

Modèl	GVW (Kg)	Volume (m3)	Length x Width x Height (body shell)	Overall Width	Loading Height	Wheels
REV2-1500	2500	1,2 / 1,7	2m50 x 0m80 x 0m60	1,16	1m26 (+0m25)	200/60-14.5
REV2-1800	3200	1,5 / 2,1	2m50 x 1m00 x 0m60	1,36	1m49 (+0m25)	205 x 16
REV2-2500	3200	2,3 / 3,3	3m00 x 1m30 x 0m60	1,66	1m41 (+0m25)	10.0/75-15.3 14 ply
REV2-3500	4500	2,9 / 4,1	3m50 x 1m40 x 0m60	1,76	1m41 (+0m25)	10.0/75-15.3 14 ply

Options available :

Cover



Steered axel



Hydraulic spreading table



Mechanical spreading table

