

RES Spreader Range

Our Roche RES2 spreader range is specially designed for all uses that need to deal with height constraints: fruit farming, market gardening ...

Our models are multipurpose: with 2 horizontal beaters they can handle straw manure as well as compost.

The hydraulic drive conveyor combined with beater(s) ensure that materials are spread with a regular feed system.

Our table system (optional) gives greater flexibility in terms of spreading options both in the open field or for localised work.

Standard model

- 2 horizontal beaters (mechanical drive)
- Hydraulic drive conveyor; flow-rate control device
- Tube chain conveyor (two-chain)
- Standard wheels
- Standard Cardan shaft
- Front grill guard
- Mechanical and hydraulic brakes
- Lights, Approved for road use - 25 km/h



Options available

- Cover
- Hinged side flaps
- Hydraulic sliding door
- Mechanical spreading table
- Tapered extensions
- 2 vertical beaters
- (1.2 m-wide body shell — overall width 1.9m depending on the wheels)
- 1 hydraulic horizontal beater

RES2 4001 with extra features :
 1 hydraulic beater, mechanical spreading table,
 low-pressure tyres (380/55-17)

Modèl	GVW (Kg)	Volume (m3)	Length x Width x Height (body shell)	Overall Width	Loading Height	Wheels
RES2-2500	3200	1,9 / 2,9	3m00 x 1m30 x 0m50	2m00	1m30 (+0m25)	205 x 15
RES2-4000	5200	2,4 / 3,6	3m50 x 1m40 x 0m50	2m09	1m22 (+0m25)	10.0/75-15.3 14 ply
RES2-4001	5200	2,8 / 4,2	4m00 x 1m40 x 0m50	2m25	1m35 (+0m25)	11.5/80-15.3 14 ply

Options available :

2 vertical beaters



Tapered extensions



Hinged side flaps



Mechanical spreading table

