

# E Spreader Range

All the spreaders in our E range come with 2 angled screw rotors. They are designed for those seeking mobility and versatility, especially for easier manoeuvring on steep slopes where the conveyor guidance system and low-level chassis come into full use. The volume of the blades helps to ensure that materials are cut up more finely. The lower discs and prongs help release powdery materials evenly.

### Standard model

- 2 vertical angled screw rotors
- Hydraulic drive conveyor; flow-rate control device
- Tube chain conveyor (two-chain)
- Tractor-type wheels
- Wide-angle Cardan shaft
- Front grill guard
- Mechanical and hydraulic brakes
- Lights, approved for road use - 25 km/h



E 40 hydraulic door option

### Options available

- Hydraulic rear swing 'up-and-over' door
- Spring-loaded towbar
- Hinged side flaps
- Hydraulic parking stand
- Electric conveyor control
- Hydraulic power unit


Model	GVW (kg)	Volume (m3)	Length x Width x Height (body shell)	Loading Height	Wheels
E30	4500	3,0 / 4,1	3m50 x 1m26 x 0m70	1m40 (+0m25)	11.5/80-15.5 14 ply
E40	5990	4,0 / 5,2	3m80 x 1m26 x 0m85	1m64 (+0m25)	380/70 R 28
E55	8000	5,8 / 7,2	4m25 x 1m26 x 1m10	1m96 (+0m25)	16.9-28 12 ply
E65	10000	8,9 / 10,5	4m40 x 1m50 x 1m35	2m25 (+0m25)	16.9-28 12 ply

#### Options available :

Hydraulic door



Hydraulic power unit



Hinged side flaps

