

RE Spreader Range

The spreaders in our RE range are robust, economical and timeless.
 Highly versatile, they can be used to spread composted as well as straw materials.
 They are particularly suited to small and medium-sized farms, using tractors under 100 HP.

Standard model

- 2 horizontal beaters (mechanical drive)
- Hydraulic drive conveyor ; flow-rate control device
- Tube chain conveyor (two-chain)
- Standard wheels
- Standard Cardan shaft
- Front grill guard
- Mechanical and hydraulic brakes
- Lights, approved for road use - 25 km/h



RE2 4000 standard model, without extra options

Options available

- Cover
- Hinged side flaps
- Steered axel
- Hydraulic sliding door

Model	GVW (kg)	Volume (m3)	Length x Width x Height (One-piece body shell)	Overall Width	Loading Height	Wheels
RE2 3500	4500	3,0 /4,3	3m30 x 1m55 x 0m60	2m00	1m55 (+0m25)	10.0/75-15.3 14 ply
RE2 4000	5200	3,6 / 5,2	3m50 x 1m75 x 0m60	2m20	1m55 (+0m25)	10.0/75-15.3 14 ply
RE2 4800	5990	4,2 / 5,9	4m00 x 1m75 x 0m60	2m20	1m62 (+0m25)	11.5/85-15.3 14 ply

Options available :

Cover



Hinged side flaps

