

PRODUCT DESCRIPTION

MANURE Spreader Range

The equipment in this range is specially designed for spreading calibrated materials as well as powders: manure, granules, pellets, lime...

A rubber conveyor at the base of the hopper moves materials thanks to its 2 discs.
 Deflectors enable you to spread either on a localised area, or across the whole width.

Standard model

- Fully hydraulic
- Rubber hydraulic drive conveyor; flow-rate control device
- Hydraulic spreading table
- Front grill guard
- Mechanical and hydraulic brakes
- Lights, approved for road use - 25 km/h

Options available

- Articulated drawbar
- Extensions (0.25 m)
- Sizing grid
- Oil filter (input pressure)
- Valve with hydraulic opening system



EEV2 tractor-type wheels option

Model	GVW (kg)	Volume (m3 - water)	Length x Width x Height (body shell)	Overall Width	Loading Height	Wheels
EEV 2	2500	1,2 / 1,9	2m55 x 1m20 x 0m50	1m25	1m35 (+0m25)	10.0/75-15.3 14 ply
EEF 2	4500	1,3 / 2,5	3m00 x 1m50 x 0m40	1m70	1m25 (+0m25)	11.5/80-15.3 14 ply

Options available :

Extensions



Articulated drawbar

