

RB2-M Monocoque Trailer Range

Simple, robust and multipurpose – that’s what sums up the strength of our RB2-M range. Available in a host of different models, with payloads covering 3 to 10 tonnes, our monocoque trailers can be counted on for hauling all your bulk loads. Thanks to our extensive selection of door options, you can choose the exact vehicle to meet your needs.

Standard model

One-piece steel body
 Standard door with unlocking system from below
 Drawbar adjustable to different heights
 Mechanical and hydraulic brakes
 Lights, approved for road use - 25 km/h

Options available

Rotating drawbar
 Lift-jack or hydraulic parking stand
 Spring-loaded towbar
 Different door options (barn door, dual purpose, hydraulic lifting system → see our doors page)
 Grain hatch
 Road wheels

Model	GVW (kg)	Payload (kg)	Length x Inside Width x Height (body shell)	Loading Height	Wheels
MODEL with single set of wheels					
RB2-3500-M	4500	3500	3m10 x 1m50 x 0m80		10.0/75-15.3 14 ply
RB2-4001-M	5200	4000	3m50 x 1m70 x 0m80	1m64	10.0/75-15.3 14 ply
RB2-4002-M	5200	4000	3m50 x 1m90 x 0m80	1m68	11.5/80-15.3 14 ply
RB2-4800-M	5990	4800	4m00 x 1m90 x 0m80	1m70	11.5/80-15.3 14 ply
RB2-5500-M	7000	5500	4m00 x 2m10 x 0m80	1m76	12.5/80-15.3 14 ply
RB2-6500-M	8000	6500	4m00 x 2m10 x 1m00	2m00	13.5/75-430.9 14 ply
RB2-8000-M	10000	8000	4m50 x 2m20 x 1m00	2m20	15 x 22.5
MODEL with double wheels (Rocking axle or Boggie)					
RB4-8000-M	11000	8000	4m50 x 2m20 x 1m00	2m07	12.5/80-15.3 14 ply
RB4-10000-M	13000	10000	4m50 x 2m20 x 1m00		13.5/75-430.9 14 ply

Models and Options Available:

RB2-5500-M



RB2-5500-M
Option: barn door



RB2-6500-M
Option: dual function door



Option :
Hydraulic lifting door

