

Flatbed Trailer Range

Our RP range covers a choice of flatbed trailers that are semi-mounted, and available as either 2 or 4-wheel models, depending on the load capacity. They are equipped with harvest ladders that are either tilted or straight, and specially adapted for fruit farming / market gardening. We have designed them to be as low to the ground as possible to make it easier to load and unload and to ensure greater stability.

Standard model

Simple, smooth flatbed
 Mechanical and hydraulic brakes
 Lights, approved for road use - 25 km/h

Options available

Harvest ladders for round bales
 Straight harvest ladders
 Spring-loaded towbar
 Side wideners
 4 front bale racks
 Strap box



Model	GVW (kg)	Standard Payload	Length x Width Simple flatbed	Height of Flatbed	Wheels
MODEL with single set of wheels					
RP2 3000	3700	3000	3m50 x 2m00	0m72 (environ)	10.0/75-15.3 14 ply
RP2 4000	5200	4000	5m00 x 2m00	0m74 (environ)	10.0/75-15.3 14 ply
RP2 5000	5990	5000	6m10 x 2m40	0m82 (environ)	11.5/80-15.3 14 ply
RP2 6000	7000	6000	6m10 x 2m40	0m88 (environ)	12.5/80-15.3 14 ply
MODEL with double wheels (Rocking axle or Boggie)					
RP4 7000	8700	7000	6m10 x 2m40	1m05 (environ)	11.5/80-15.3 14 ply
RP4 7001	8700	7000	7m30 x 2m40	1m05 (environ)	11.5/80-15.3 14 ply
RP4 8500	11000	8500	6m10 x 2m40	1m05 (environ)	11.5/80-15.3 14 ply
RP4 8501	11000	8500	7m30 x 2m40	1m05 (environ)	11.5/80-15.3 14 ply
RP4 10000	13000	10000	6m10 x 2m40	1m20 (environ)	13.5/75-430.9 14 ply
RP4 10001	13000	10000	7m30 x 2m40	1m20 (environ)	13.5/75-430.9 14 ply
RP4 13000	16400	13000	8m10 x 2m40	1m30 (environ)	15 x 22.5

RP2 3000

RP2 4000

RP4 6000

RPB4 130000

