

RFH Hydraulic Fruit Farming Range

When hand picking fruit, the time and method used to load and unload your harvest can have a major impact on productivity. This is why we have developed our RFH range.

Its variable height function means you can either lay the flatbed on the ground, or lift it to the same level as a loading platform or truck deck.

The two separate arms help keep the bed steady while moving over uneven surfaces.

Finally, for those wishing to keep their harvest in optimal condition, our four-wheel models and pneumatic shock absorber will ensure your fruit is kept unspoiled.

Standard model

Separate hydraulic drawbar and wheels
Surrounded by a mudguard
Front drop side
Drawbar adjustable to different heights
Mechanical and hydraulic brakes
Lights, approved for road use - 25 km/h

Elevation 0.6 or 1.2 m depending on the model
Two-wheel or four-wheel model



RFH2 3120—flatbed 4.2 m —elevation 1.2 m

Options available

Roller conveyor
Air suspension - elevation (0.6 m)
Electric-controlled power unit

Model	GVW (kg)	Payload (kg)	Number of pallets	Length x Width	Overall width	Elevation	Wheels
MODEL with single set of wheels							
RFH2 3060	5200	3500	4	4m20 x 1m25	2m25	0,00 à 0,60 m	10.0/75-15.3 14 ply
RFH2 3120	5200	3500	4	4m20 x 1m25	2m25	0,00 à 1,20 m	10.0/75-15.3 14 ply
MODEL with double wheels							
RFH2 3061	5200	3500	5	5m20 x 1m25	2m43	0,00 à 0,60 m	11.5/80-15.3 14 ply
RFH2 3121	5200	3500	5	5m20 x 1m25	2m43	0,00 à 1,20 m	11.5/80-15.3 14 ply
RFH4 3121	5200	3500	5	5m20 x 1m25	2m38	0,00 à 1,20 m	10.0/75-15.3 14 ply

RFH2 3061 with air suspension option

RFH4 3161

