



# E Spreader Range

All the spreaders in our E range come with 2 angled screw rotors.

They are designed for those seeking mobility and versatility, especially for easier manoeuvring on steep slopes where the conveyor guidance system and low-level chassis come into full use.

The volume of the blades helps to ensure that materials are cut up more finely. The lower discs and prongs help release powdery materials evenly.

## Standard model

2 vertical angled screw rotors (**mechanical drive**) (**540 revolutions per minute**)

Hydraulic drive conveyor; flow-rate control device

Tube chain conveyor (two-chain)

Tractor-type wheels

Wide-angle Cardan shaft

Front grill guard

Mechanical and hydraulic brakes (**dual hydraulic line + mandatory ABS connection on the tractor**)

Lights, approved for road use - 25 km/h

| Model      | GVW (kg) | Volume    | Length x Width x Height | Overall | Loading Height | Wheels              |
|------------|----------|-----------|-------------------------|---------|----------------|---------------------|
| <b>E30</b> | 4500     | 3,0 / 4,1 | 3m50 x 1m26 x 0m70      |         | 1m40 (+0m25)   | 11.5/80-15.5 14 ply |
| <b>E40</b> | 6700     | 4,0 / 5,2 | 3m80 x 1m26 x 0m85      |         | 1m64 (+0m25)   | 14.9-24 14 ply      |
| <b>E55</b> | 8000     | 5,8 / 7,2 | 4m25 x 1m26 x 1m10      |         | 1m96 (+0m25)   | 16.9-28 12 ply      |
| <b>E65</b> | 10000    | 7,6 / 9,7 | 4m40 x 1m50 x 1m35      |         | 2m25 (+0m25)   | 16.9-28 12 ply      |



**E.55**

with options : electric conveyor control, spring-loaded

## Options available

Hydraulic rear swing 'up-and-over' door

Spring-loaded towbar

Hinged side flaps

Hydraulic parking stand

Electric control (1 or 2 function)

Hydraulic power unit

**Compteur heure pressostat (avec simple affichage : compte les heures de travail au total)**

## Options available :

Hydraulic door



Spring-loaded towbar



Hinged side flaps



Hydraulic power unit



ROCHE PÈRE ET FILS - 32 Route de Crest - 26400 Aouste-sur-Sye (FRANCE)

Tél. +33 (0)4 75 25 14 72 Fax. +33 (0)4 75 25 00 30 - E-mail : [contact@remorques-roche.com](mailto:contact@remorques-roche.com)