



REV Spreaders Range

Our REV range is specially designed for all types of farming that need to deal with width constraints: vineyards, espaliered orchards, market gardening rows ... The steered axel feature makes our models extremely easy to manoeuvre, especially at the end of rows where there is little turning space. The spreading tables allow you to deposit materials at the base of vines or espaliered trees, or spread along several rows at a time.

Standard model

2 horizontal beaters (mechanical drive) (540 revolutions per minute)
 Hydraulic drive conveyor; flow-rate control device
 Tube chain conveyor (two-chain)
 Standard wheels
 Standard Cardan shaft
 Front grill guard
 Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)
 Lights, approved for road use - 25 km/h

Modèl	GVW (Kg)	Volume (m3)	Length x Width x Height (body shell)	Overall Width	Loading Height	Wheels
REV2-1800	3200	1,5 / 2,2	2m50 x 1m00 x 0m60	1,36	1m49 (+0m30)	10.0/75-15.3 14 ply
REV2-2500	3200	2,3 / 3,5	3m00 x 1m30 x 0m60	1,66	1m41 (+0m30)	10.0/75-15.3 14 ply
REV2-3500	4500	2,9 / 4,4	3m50 x 1m40 x 0m60	1,76	1m41 (+0m30)	10.0/75-15.3 14 ply
REV2-4000	5200	3,3 / 5,0	4m00 x 1m40 x 0m60	1,76	1m41 (+0m30)	11.5/80-15.3 14 ply



REV2 3500

with option : aluminum extensions

Options available

Cover
 Hinged side flaps
 Steered axel
 Hydraulic sliding door
 Hydraulic or mechanical spreading table, depending on the size of the body shell
 2 vertical beaters (1.2 m-wide body shell)

Options disponibles :

Steered axel



Mechanical Table



Hydraulic Table



2 vertical beaters

