



The spreaders in our RE range are robust, economical and timeless.
Highly versatile, they can be used to spread composted as well as straw materials.
They are particularly suited to small and medium-sized farms, using tractors under 100 HP.

Standard model

2 horizontal beaters (mechanical drive) (540 revolutions per minute)
Hydraulic drive conveyor ; flow-rate control device
Tube chain conveyor (two-chain)
Standard wheels
Standard Cardan shaft
Front grill guard
Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)
Lights, approved for road use - 25 km/h

Model	GVW (kg)	Volume (m3)	Length x Width x Height (One-piece body shell)	Overall Width	Loading Height	Wheels
RE2 3500	4500	3,0 / 4,3	3m30 x 1m55 x 0m60	2m00	1m55 (+0m25)	10.0/75-15.3 14 ply
RE2 4000	5200	3,6 / 5,2	3m50 x 1m75 x 0m60	2m20	1m55 (+0m25)	10.0/75-15.3 14 ply
RE2 4800	5990	4,2 / 5,9	4m00 x 1m75 x 0m60	2m20	1m62 (+0m25)	11.5/85-15.3 14 ply



RE2 4000

Options available

Cover
Hinged side flaps
Steered axel
Hydraulic sliding door
The branches slide

Options available :

Cover



Hinged side flaps



Hydraulic sliding door

