



FERTILIZER Spreader Range

The equipment in this range is specially designed for spreading calibrated materials as well as powders: manure, granules, pellets, lime...
A rubber conveyor at the base of the hopper moves materials thanks to its 2 discs.
Deflectors enable you to spread either on a localised area, or across the whole width.

Standard model

Fully hydraulic
Rubber hydraulic drive conveyor; flow-rate control device (540 revolutions per minute)
Hydraulic spreading table
Front grill guard
Valve with hydraulic opening system
Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)
Lights, approved for road use - 25 km/h

Model	GVW (kg)	Volume (m3 - water)	Length x Width x Height (body shell)	Overall Width	Loading Height	Wheels
EEV 2	2500	1,2 / 1,9	2m55 x 1m20 x 0m50	1m25	1m35 (+0m25)	10.0/75-15.3 14 ply
EEF 2	4500	1,3 / 2,5	3m00 x 1m50 x 0m40	1m70	1m25 (+0m25)	11.5/80-15.3 14 ply



EEF 2

with options : extensions + low-pressure tyres

Options available

Extensions (0.25 m)
Sizing grid
Oil filter (input pressure)
DPA

Options available :

Oil filter (input pressure)

DPA

Sizing grid

