



Our range of trailers designed for working between rows
come in several different models, all specifically for hand

Winegrowing Trailer Range For Working Between Rows

Standard model : Tombereau

One-piece steel body - Interior coated with food grade paint

Extensions (0.3 m)

Hydraulic door control system

Drawbar adjustable to different heights

Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)

Lights, approved for road use - 25 km/h

Model	GVW (kg)	Body Capacity	Length x Overall Width x	Loading Height	Wheels
Tombereau					
T 2500	3200	2434	2m50 x 1m30 x 0m60 + 0m30	1m20 + 0m30	10.0/75-15.3 14 ply
T 3000	3700	2920	3m00 x 1m30 x 0m60 + 0m30	1m20 + 0m30	10.0/75-15.3 14 ply
Petite benne interligne					
RBM2 2000	3200	2014	2m50 x 1m50 x 0m60	1m42	10.0/75-15.3 14 ply
RBM2 3000	3700	2147	3m00 x 1m50 x 0m60	1m42	10.0/75-15.3 14 ply
Tray + Container					
RBE2 2500	3200	2023	2m50 x 1m50 x 0m60	0m82 + 0m60	10.0/75-15.3 14 ply
RBE2 3000	3700	2769	3m00 x 1m70 x 0m60	0m82 + 0m60	10.0/75-15.3 14 ply
RBE2 3500	4500	3110	3m00 x 1m90 x 0m60	0m82 + 0m60	10.0/75-15.3 14 ply

Standard model : RBE (tray + container)

One-piece steel flatbed trailer + container

Interior coated with food grade paint

Standard watertight door (lever-action opening)

Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)

Lights, approved for road use - 25 km/h



Tombereau

Options available :

Rotating drawbar
Stainless steel model



Tray + container

