



# SD-SDE Direct Harvesting Range

The direct harvesting trailers in our R.SD and R.SDE range are designed for those with more challenging needs - namely those seeking to maintain the quality of the grapes from the vine all the way to the wine cellar.

The variable-speed worm-type conveyor system ensures that the grapes take the smoothest possible path and remain unspoiled.

They come in standard or lifting models, in steel or stainless steel.

## Standard model

One-piece steel body with an Archimedes screw (diameter - 300 mm)

Hydraulic engine drive by dual action tractor (**540 revolutions per minute**)

Standard door (lever-action opening) (for SD) Hydraulic door (for SDE obligatoire)

Mechanical and hydraulic brakes (**dual hydraulic line + mandatory ABS connection on the tractor**)

Lights, approved for road use - 25 km/h

| Model                          | GVW (kg) | Body Capacity (litre) | Length x Outside Width x Height (body shell) | Loading Height | Wheels              |
|--------------------------------|----------|-----------------------|----------------------------------------------|----------------|---------------------|
| <b>MODELE à sortie directe</b> |          |                       |                                              |                |                     |
| <b>R 250 SD</b>                | 3200     | 2541                  | 2m50 x 1m30                                  |                | 205 x 16            |
| <b>R 300 SD</b>                | 3700     | 3023                  | 2m75 x 1m50                                  |                | 10.0/75-15.3 14 ply |
| <b>R 400 SD</b>                | 5200     | 4027                  | 3m00 x 1m90                                  |                | 11.5/80-15.3 14 ply |
| <b>R 500 SD</b>                | 5990     | 5048                  | 3m00 x 2m00                                  | 1m82           | 11.5/80-15.3 14 ply |
| <b>MODELE double roues</b>     |          |                       |                                              |                |                     |
| <b>R 250 SDE</b>               | 3200     | 2516                  | 2m50 x 1m30                                  | 1m53           | 205 x 16            |
| <b>R 300 SDE</b>               | 3700     | 2991                  | 2m75 x 1m50                                  | 1m56           | 10.0/75-15.3 14 ply |
| <b>R 400 SDE</b>               | 5200     | 4147                  | 3m00 x 1m90                                  |                | 10.0/75-15.3 14 ply |

## Options available

Rotating drawbar

Rear lever-controlled power unit, reverse switch and flow-rate control device

Hydraulic gear motor drive

Hydraulic door

Stainless steel model



**R 500 SD**  
with standard door

## Options available :

Lifting model



Hydraulic door



Stainless steel model

