



E2-R et E2-M Lifting Trailer Range

We have a range of lifting and tipping trailers all fitted with a simple Z-type lifting system. They come in monocoque models as well as drop side flatbed models.

Standard model

Drop side model

Flatbed - Drop sides - Door control system opening from below

Monocoque model

One-piece stainless steel body - Hydraulic door control system

Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)

Lights, approved for road use - 25 km/h

Model	GVW (kg)		Loading Height	Elevation	Wheels
Drop side model		Standard payload	Length x Width simple flatbed without drop sides		
E2-3000-R	3700	3000	3m00 x 1m50 / 0m50	1m32	10.0/75-15.3 14 ply
E2-4800-R	5990	4800	3m50 x 1m90 / 0m80	1m70	2m00 11.5/80-15.3 14 ply
E2-4801-R	5990	4800	4m00 x 1m90 / 0m80	1m70	2m00 11.5/80-15.3 14 ply
E2-6000-R	8000	6000	4m00 x 2m10 / 0m50	1m50	13.5/75-430.9
Monocoque MODEL		Max Volume	Length x Inside Width x Height		
E2-3000-M	3700	3,6	3m00 x 1m50 x 0m80	1m62	10.0/75-15.3 14 ply
E2-4800-M	5990	5,3	3m50 x 1m90 x 0m80	1m70	2m00 11.5/80-15.3 14 ply
E2-4801-M	5990	6,0	4m00 x 1m90 x 0m80	1m70	2m00 11.5/80-15.3 14 ply
E2-6000-M	8000	6,7	4m00 x 2m10 x 1m00	2m02	315/60 R 22.5



E2-4800-R

with options : **trappe à grain**, extensions

Options disponibles

Rotating drawbar
Spring-loaded drawbar
Lift-jack or hydraulic parking stand
Other extra options available (on request)

