



RFH Hydraulic Fruit Farming Range

When hand picking fruit, the time and method used to load and unload your harvest can have a major impact on productivity. This is why we have developed our RFH range. Its variable height function means you can either lay the flatbed on the ground, or lift it to the same level as a loading platform or truck deck.

The two separate arms help keep the bed steady while moving over uneven surfaces.

Finally, for those wishing to keep their harvest in optimal condition, our four-wheel models and pneumatic shock absorber will ensure your fruit is kept unspoiled.

Standard model

Elevation 0.6 or 1.2 m depending on the model - Electric-controlled power unit

Separate hydraulic drawbar and wheels

Surrounded by a mudguard

Front drop side

Mechanical and hydraulic brakes (dual hydraulic line + mandatory ABS connection on the tractor)

Lights, approved for road use - 25 km/h

Model	GVW (kg)	Payload (kg)	Number of pallets	Length x Width	Elevation	Wheels
MODEL with single set of wheels						
RFH2 3060	5200	3500	4	4m20 x 1m25	0,00 à 0,60 m	10.0/75-15.3 14 ply
RFH2 3120	5200	3500	4	4m20 x 1m25	0,00 à 1,20 m	10.0/75-15.3 14 ply
RFH2 3061	5990	3500	5	5m20 x 1m25	0,00 à 0,60 m	11.5/80-15.3 14 ply
RFH2 3121	5990	3500	5	5m20 x 1m25	0,00 à 1,20 m	11.5/80-15.3 14 ply
MODEL with double wheels						
RFH4 3121	5900	3500	5	5m20 x 1m25	0,00 à 1,20 m	10.0/75-15.3 14 ply



RFH2 3120

with option : low-pressure tyres

Options available

Roller conveyor

Air suspension

Ridelles claire-voie

Options disponibles :

Roller conveyor



Air suspension



Ridelles claire-voie



ROCHE PÈRE ET FILS - 32 Route de Crest - 26400 Aouste-sur-Sye (FRANCE)

Tél. +33 (0)4 75 25 14 72 Fax. +33 (0)4 75 25 00 30 - E-mail : contact@remorques-roche.com